



1-CUBE s. r. o.

Hamry 3567, 580 01 Havl. Brod, Czech Republic

tel + 420 569 433620, fax + 420 569 422144

e-mail: 1-cube @ 1-cube.com web site: www.1-cube.com

DECARBONIZER - OP

Technical Description and Use:

- Prepares samples for analysis
- Provides a fast and accurate check on the course of fermentation in cylindro-conical fermenters and maturation tanks.

Nearly all the chemical analysis of beer or saturated drinks which demands the removal of CO₂, can be used with the defoamer. This apparatus can prepare a 150 ml sample for analysis in 1 minute and when in connection with an aseptic sampling valve and saccharimeter, makes it possible to quickly and accurately determine the grade of fermentation in cylindro-conical fermenters.

This equipment makes it possible to carry out a fast decarbonization on beer samples or saturated drinks. Decarbonization is carried out by mixing. The equipment consists of a transparent Lucite vessel with an outlet valve for the decarbonized sample, a top with a mixer and electronics. The set timer can be utilized for obtaining a level degree of decarbonization or as required.



Model:

OP

Technical parameters:

Volume of decarbonized sample.....max. 150 ml
CO₂ content after decarbonizationmax. 0,05%
Decarbonization time..about 1 min

Base Model:

Apparatus - 1 piece

Optional Accessories:

A glass measuring vessel for specific volume
Densimeters with range..0 - 7%
7 - 13 %

Note: Accessories may be purchased as required.